

## Introduction

<b>MELTRIC Overview</b>	pg 2
<b>Product Features &amp; Benefits</b>	pg 4
<b>Product Summary &amp; Selection Guide</b>	pg 8
<b>Part Number &amp; Ordering Guide</b>	pg 14
<b>Switch-Rated Plugs &amp; Receptacles</b>	
<b>The Main Differences</b>	pg 16
<b>Selection Guide</b>	pg 20
<b>DSN</b> Type 4X/IP69k rated, metal or poly casings. From 20 – 150A (1/2 – 75 hp)	pg 22
<b>DS</b> Type 3R rated, metal or poly casings. From 20 – 200A (3/4 – 100 hp)	pg 38
<b>DB</b> IP67 rated, metal casings. From 30 – 100A (2 – 60 hp)	pg 56

## Multipin Plugs & Receptacles

<b>Multipin</b> 4 – 37 pin connectors in poly and metal. From 2 – 150A	pg 70
--	-------

## Standard Duty Plugs & Receptacles

<b>DR</b> Type 3R rated, poly or metal casings. From 30 – 400A	pg 96
<b>PN</b> IP66/IP67 rated or IP54 rated, poly or metal. 20A	pg 114
<b>High Temp</b> For environments up to 465°F (240°C)	pg 122

## Direct Current Plugs & Receptacles

<b>DSDC</b> DC current rated, poly or metal casings. Up to 750 VDC	pg 126
--	--------

## High Ampacity Plugs & Receptacles

<b>PF/PFQ</b> IP66/IP67 rated, metal construction. From 300 – 600A	pg 132
<b>DR400</b> Type 3R rated, metal casings. 400A	pg 140
<b>SP</b> Single pole, connectors up to 600A	pg 144
<b>CS1000</b> Single pole, connectors up to 400A	pg 148

## Power Distribution

<b>Custom Power Distribution Solutions</b> Built specifically to meet customer needs	pg 154
<b>Integral Circuit Protection Wall Boxes</b> Premounted receptacles wired to circuit protection 20-60A	pg 162
<b>GFCI Combinations</b> Premounted receptacles wired to GFCI boxes 20-60A	pg 168
<b>Safety Switch/Receptacle Combinations</b> Switch-rated receptacles mounted to single throw, fusible safety switch	pg 170

## Specialty Products

<b>WS – Welding Connectors</b> Single pole connectors (max 50 VAC)	pg 174
<b>Adapter Plates</b> For converting existing receptacles to MELTRIC	pg 175
<b>Cord Grips</b>	pg 178
<b>Voltage/Phase Rotation Meter Assemblies</b>	pg 180

## Hazardous Location Plugs & Receptacles

<b>Hazardous Duty Selection Guide</b>	pg 184
<b>DXN</b> Hazardous rated, poly casings. From 20 – 60A (1/4 – 20 hp)	pg 186
<b>DXA</b> Hazardous rated, metallic casings. From 20 – 100A	pg 198
<b>DSN/DS/DR/DSDC</b> Hazardous rated, metallic casings. 2 – 250A (up to 100 hp)	pg 202
<b>DX</b> Hazardous rated, metallic casings. From 20 – 125A	pg 226
<b>Multipin</b> Hazardous rated, 12 to 37 pins, 10A	pg 236
<b>SPeX</b> Hazardous rated, up to 680A, 1000VAC	pg 242