# PN12c Multipin Plugs & Receptacles – 7.5A

## **Ratings**

- Voltage 600 VAC Max/130 VDC
- Amperage Rating 5A Current Interrupting 7.5A Non-Current Interrupting
- ! PN12c is capable of handling 4-20mA low current applications
- Environmental Ratings \* IP66/IP67 (Poly/Metal)
- Temperature Range Min -40°F / Max 140°F See pg 271 for temps below -15°F.
- Wiring Capacity Min 18 AWG Max 14 AWG
- Certifications UL Coming Soon!



Don't forget to add installation

accessories to your order

# **North American Configurations**

		Part #			Part #		
Voltage	Polarity	Poly	Metal	Stainless Steel	Poly	Metal	Stainless Steel
600V	11P+G	03-A4001	07-A4001	07-A4001-SS	03-A8001	07-A8001	07-A8001-SS

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact customer service at 800.433.7642.

Main Options	
	Reverse Interiors
0	Flush Mount (replaces female casing)
	Locking Pawl

Receptacle Options	Suffix #	Inlet Options	Suffix #
Reverse Interiors	Recept # - 001	Reverse Interiors	Inlet # - 001
With Flush Mount (poly only)	Recept # - 142*		
Locking Pawl	Recept # - 824-300		

\* IP55 rating with Flush Mount casing



Order Example: 600V PN12c + Reverse Interiors

PN12c Receptacle 11P+G = 03-A4001**-001** 

# **INSTALLATION ACCESSORIES - SIZE 1**

Unless indicated otherwise, accessories can be used with either poly or metal plugs and receptacles

**HANDLES** 

HANDLE w/N	IPT	Part # Poly	Part # Metal
1/2" 3/4" 1"	1/2"	511P0N05	591P0N05
	3/4"	511P0N07	591P0N07
	511P0N10	591P0N10	

HANDLE w/CO	ORD GRIP Cable Range	Poly	Metal
	.438500"	711P0BP3	791P0BS3
	.500562"	711P0BP4	791P0BS4
and the same	.562625"	711P0BP5	791P0BS5
	.625750"	711P0CP4	791P0CS4

90° NTLUN	HANDLE INTEA	iaea Opening W/NP
	1/2"	751P9N05
4	3/4"	751P9N07

10	1/2"	751P9N05
	3/4"	751P9N07
	1"	751P9N10

STAIN	ESS S	STEEL	HANDL	E w/NPT	

	1/2"	7X1P0N05	For 1/2" NPT size, a
9=	3/4"	7X1P0N07	hole size reducer is utilized
	1"	7X1P0N10	

### NYLON HANDLE w/Cable Range

.3570"	511P0D18	



For available cord grips, see pg 178 For a guideline of NPT based cable ranges, see PN7c on pg 75.

ANGLES

1		
	30° for MB Box	511M3

O	0°	591M0	
			* Base measures

approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not cal Customer Service for

			other solutions.
	45°	591M4	
STAINLESS ST	EEL ANGLE		

30° 7X1M4 BOXES

	POLY CONDUIT ENTRY w/NPT			Part #	
		30°	1/2"	511B3N05	* Interior volume with
'	* 6.9 in <sup>3</sup>	30°	3/4"	511B3N07	receptacle installed.
	POLY WALL BO	OX w/NPT			
		0°	1/2"	511B0N05	* Interior volume with
	* 3.4 in <sup>3</sup>	0°	3/4"	511B0N07	receptacle installed.
	METAL WALL	BOX w/NPT			
	4	0°	1/2"	591B0N05	* Interior volume with
	* 3.7 in <sup>3</sup>	0°	3/4"	591B0N07	receptacle installed.
	POLY WALL BO	OX w/NPT			
	* 82.0 in <sup>3</sup>	70°	1/2" - 1 1/4"	511C7000	70° poly boxes are not drilled. Contact cus- tomer service if factory drilled is required. * Interior volume with receptacle installed.
	METAL BOX w	/NPT			
		0°	1/2"	7T1F0N05	
		0°	3/4"	7T1F0N07	

	0°	1/2"	7T1F0N05
	0°	3/4"	7T1F0N07
	0°	1"	7T1F0N10
	0°	1 1/4"	7T1F0N12

METAL BOX W	ITH NYLON AN	IGLE W/
(0	30°	1/2"
	30°	3/4"
	30°	1"

\* Interior volume with receptacle installed.

METAL BOX V	VITH MET	AL ANGLE w
C C	45°	1/2"
	45°	3/4"

30°

45°	1/2"	791C4N05	
45°	3/4"	791C4N07	* Interior volume with
45°	1"	791C4N10	receptacle installed.
45°	1 1/4"	791C4N12	

711C3N05 711C3N07

711C3N10 711C3N12

1 1/4"

1120	30°	3/4"	7X1C3N07
	30°	1"	7X1C3N10

\* Includes angle adapter as shown.

# **MISCELLANEOUS ACCESSORIES** PROTECTIVE CAP

\* 30.0 in<sup>3</sup>

\* 26.9 in<sup>3</sup>

		01-2A126	Will not fit devices with reverse interiors. For Male Devices Only.
	FLUSH MOUNT		
	(		



01-2A142

see page 178

MULTI-CONTACT REMOVAL TOOL

61-CA593



61-CA500

4CN30