






MELTRIC PRODUCT SUMMARY...




	Model	Amp Rating	Maximum Voltage Rating		Environmental Ratings		Available Casing Materials			Maximum Number of Contacts	
			VAC	VDC	Type	IP	Poly	Metal	SS	Main	Aux.
Switch-Rated	 DSN20	20	600	-	4X	69k	Poly	-	-	3P+N+G	2
	DSN30	30	600	-	4X	69k	Poly	-	-	3P+N+G	2
	DSN60	60	600	-	4X	69k	Poly	-	-	3P+N+G	4
	DSN150	150	600	-	4X	69k	Poly	Metal	-	3P+N+G	6
	DS20	20	600	-	3R	-	Poly	-	-	3P+N+G	2
	DS30	30	600	-	3R	-	Poly	-	-	3P+N+G	4
	 DS60	60	600	-	3R	-	Poly	Metal	-	3P+N+G	4
	DS100C	100	600	-	3R	-	Poly	Metal	-	3P+N+G	4
	DS100	100	600	-	3R	-	Poly	Metal	-	3P+N+G	6
	DS200	200	600	-	3R	-	-	Metal	-	3P+N+G	6
	DB30	30	600	-	-	67	-	Metal	-	3P+N+G	2
	DB60	60	600	-	-	67	-	Metal	-	3P+N+G	2
	DB100	100	600	-	-	67	-	Metal	-	3P+N+G	4
Multipin	 PN7c	15	600	130	-	66/67*	Poly	Metal	SS	6P+G	-
	PN7c	20	600	130	-	66/67*	Poly	Metal	SS	6P+G	-
	PN12c	5	600	-	-	66/67*	Poly	Metal	SS	11P+G	-
	PN12c	7.5	600	-	-	66/67*	Poly	Metal	SS	11P+G	-
	DSN24c	2	480	130	-	66/67	Poly	-	-	24	-
	DSN24c	7.5	480	130	-	66/67	Poly	-	-	24	-
	DS24c	2	250	130	-	-	-	-	SS	24	-
	DS24c	7.5	250	130	-	-	-	-	SS	24	-
	 DSN37c	2	480	130	-	66/67	Poly	-	-	37	-
	DSN37c	7.5	480	130	-	66/67	Poly	-	-	37	-
	DS37c	2	480	130	-	-	-	-	SS	37	-
	DS37c	7.5	480	130	-	-	-	-	SS	37	-
	 DN9c	20	480	130	-	54/55	-	Metal	-	9	-
	DN20c	20	480	130	-	54/55	-	Metal	-	20	-
	DS7c	30	600	130	-	54/55	Poly	Metal	-	7	3
DR7c	50	600	130	-	54/55	Poly	Metal	-	7	3	

...AND SELECTION GUIDE

Model	Current Interruption Rating*	Horsepower Ratings (see catalog section for other voltages)			Main Contacts Wire Size Capacity		Terminal Type
		240V - 3Ø	480V - 3Ø	600V - 3Ø	Min	Max	
DSN20	Switch-Rated	2 hp	5 hp	5 hp	14 AWG	12 AWG	Screw
DSN30	Switch-Rated	5 hp	10 hp	15 hp	14 AWG	8 AWG	Screw
DSN60	Switch-Rated	7 ½ hp	20 hp	20 hp	12 AWG	4 AWG	Screw
DSN150	Switch-Rated	30 hp	75 hp	75 hp	4 AWG	2/0 AWG	Screw
DS20	Switch-Rated	5 hp	7.5 hp	10 hp	14 AWG	8 AWG	Screw
DS30	Switch-Rated	5 hp	15 hp	15 hp	14 AWG	4 AWG	Screw
DS60	Switch-Rated	10 hp	25 hp	25 hp	10 AWG	2 AWG	Screw
DS100C	Switch-Rated	20 hp	50 hp	50 hp	10 AWG	2 AWG	Screw
DS100	Switch-Rated	10 hp	30 hp	-	4 AWG	2/0 AWG	Screw
DS200	Switch-Rated	40 hp	100 hp	100 hp	4 AWG	4/0 AWG	Screw
DB30	Switch-Rated	7 ½ hp	20 hp	25 hp	14 AWG	8 AWG	Screw
DB60	Switch-Rated	15 hp	30 hp	30 hp	8 AWG	3 AWG	Screw
DB100	Switch-Rated	30 hp	60 hp	60 hp	1/0 AWG	2/0 AWG	Screw
PN7c	Current Interrupting	-	-	-	18 AWG	10 AWG	Screw
PN7c	Non-Current Interrupting	-	-	-	18 AWG	10 AWG	Screw
PN12c	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
PN12c	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DSN24c	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DSN24c	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DS24c	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DS24c	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DSN37c	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DSN37c	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DS37c	Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DS37c	Non-Current Interrupting	-	-	-	18 AWG	14 AWG	Solder/Crimp
DN9c	Current Interrupting	3 hp	5 hp	-	16 AWG	10 AWG	Screw
DN20c	Current Interrupting	1 hp	3 hp	-	16 AWG	10 AWG	Screw
DS7c	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DR7c	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw

* 'Switch-Rated' and 'Current Interrupting' ratings apply to alternating current only.

MELTRIC PRODUCT SUMMARY...

	Model	Amp Rating	Maximum Voltage Rating		Environmental Ratings		Available Casing Materials			Maximum Number of Contacts	
			VAC	VDC	Type	IP	Poly	Metal	SS	Main	Aux.
Standard 	DR30	30	600	-	3R	-	Poly	-	-	3P+N+G	2
	DR50	50	600	-	3R	-	Poly	-	-	3P+N+G	4
	DR100	100	600	-	3R	-	Poly	Metal	-	3P+N+G	4
	DR150	150	600	-	3R	-	Poly	Metal	-	3P+N+G	6
	DR250	250	600	-	3R	-	-	Metal	-	3P+N+G	6
	DR400	400	480**	-	3R	-	-	Metal	-	3P+N+G	2
	PN	15	600	-	-	55 or 66+67*	Poly	Metal	SS	3P+N+G	-
	PN	20	480	-	-	55 or 66+67*	Poly	Metal	SS	3P+N+G	-
	PNHT	30	480	-	-	44	-	Metal	-	3P+N+G	-
Direct Current 	DSDC1	20	-	250	3R	-	Poly	-	-	2P+G	0
	DSDC1	15	-	600	3R	-	Poly	-	-	2P+G	0
	DSDC1	10	-	750	3R	-	Poly	-	-	2P+G	0
	DSDC3	30	-	250	3R	-	Poly	-	-	2P+G	0
	DSDC3	30	-	600	3R	-	Poly	-	-	2P+G	0
	DSDC3	20	-	750	3R	-	Poly	-	-	2P+G	0
	DSDC6	60	-	250	3R	-	Poly	Metal	-	2P+G	0
	DSDC6	50	-	600	3R	-	Poly	Metal	-	2P+G	0
	DSDC6	30	-	750	3R	-	Poly	Metal	-	2P+G	0
	DSDC9	100	-	250	3R	-	Poly	Metal	-	2P+G	0
	DSDC9	60	-	600	3R	-	Poly	Metal	-	2P+G	0
	DSDC2	200	-	250	3R	-	-	Metal	-	2P+G	0
	DSDC2	100	-	600	3R	-	-	Metal	-	2P+G	0
High Ampacity 	PFQ	300	600	250	-	66/67	-	Metal	-	3P+N+G	8
	PF300	300	600	250	-	66/67	-	Metal	-	3P+N+G	4
	PF400	400	600	250	-	66/67	-	Metal	-	3P+N+G	4
	PF600	600	600	250	-	66/67	-	Metal	-	3P+N+G	4
	SP	600	600	1500	-	66/67	Poly	-	-	1P	-
	CS1000	400	1000	1500	-	66/67	Poly	-	-	1P	-

* The indicated ratings do not apply to devices with SS casings.

** 600V available at 350 amps.

¹ Up to 250VAC.

...AND SELECTION GUIDE

Model	Current Interruption Rating*	Horsepower Ratings (see catalog section for other voltages)			Main Contacts Wire Size Capacity		Terminal Type
		240V - 3Ø	480V - 3Ø	600V - 3Ø	Min	Max	
DR30	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DR50	Current Interrupting	-	-	-	14 AWG	4 AWG	Screw
DR100	Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
DR150	Current Interrupting	-	-	-	4 AWG	2/0 AWG	Screw
DR250	Non-Current Interrupting	-	-	-	4 AWG	4/0 AWG	Screw
DR400	Non-Current Interrupting	-	-	-	2 AWG	500 MCM	Screw
PN	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
PN	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
PNHT	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DSDC1	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DSDC1	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DSDC1	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DSDC3	Non-Current Interrupting	-	-	-	14 AWG	6 AWG	Screw
DSDC3	Non-Current Interrupting	-	-	-	14 AWG	6 AWG	Screw
DSDC3	Non-Current Interrupting	-	-	-	14 AWG	6 AWG	Screw
DSDC6	Non-Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
DSDC6	Non-Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
DSDC6	Non-Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
DSDC9	Non-Current Interrupting	-	-	-	8 AWG	2/0 AWG	Screw
DSDC9	Non-Current Interrupting	-	-	-	8 AWG	2/0 AWG	Screw
DSDC2	Non-Current Interrupting	-	-	-	4 AWG	4/0 AWG	Screw
DSDC2	Non-Current Interrupting	-	-	-	4 AWG	4/0 AWG	Screw
PFQ	Non-Current Interrupting	-	-	-	2 AWG	600 MCM	Lug
PF300	Non-Current Interrupting	-	-	-	2 AWG	600 MCM	Lug
PF400	Non-Current Interrupting	-	-	-	2 AWG	600 MCM	Lug
PF600	Non-Current Interrupting	-	-	-	2 AWG	600 MCM	Lug
SP	Non-Current Interrupting	-	500 hp	500 hp	2/0 AWG	777 MCM	Lug
CS1000	Non-Current Interrupting	-	-	-	2/0 AWG	444 MCM	Lug

* 'Current Interrupting' rating applies to alternating current only.

MELTRIC PRODUCT SUMMARY...

Hazardous Location



Model	Amp Rating	Maximum Voltage Rating		Environmental Ratings		Available Casing Materials			Maximum Number of Contacts	
		VAC	VDC	Type	IP	Poly	Metal	SS	Main	Aux.
DXN20	20	480	-	-	66/67	Poly	-	-	3P+N+G	-
DXN30	30	600	-	-	66/67	Poly	-	-	3P+N+G	2
DXN60	60	600	-	-	66/67	Poly	-	-	3P+N+G	2
DXA1	20	550	-	-	66/67	-	Metal	-	3P+N+G	-
DS20	20	600	-	4X	-	Poly	-	-	3P+N+G	2
DS30	30	600	-	4X	-	Poly	-	-	3P+N+G	4
DS60	60	600	-	4X	-	-	Metal	-	3P+N+G	4
DS100C	100	600	-	4X	-	Poly	Metal	-	3P+N+G	4
DSN150	150	600	-	4X	-	-	Metal	-	3P+N+G	6
DS200	200	600	-	4X	-	-	Metal	-	3P+N+G	6
DR30	30	600	-	4X	-	Poly	-	-	3P+N+G	2
DR50	50	600	-	4X	-	Poly	-	-	3P+N+G	4
DR100	150	600	-	4X	-	Poly	Metal	-	3P+N+G	4
DR250	250	600	-	4X	-	-	Metal	-	3P+N+G	6
DSDC1	20	-	250	4X	-	Poly	-	-	2P+G	-
DSDC3	30	-	250	4X	-	Poly	-	-	2P+G	-
DSDC6	60	-	250	4X	-	Poly	Metal	-	2P+G	-
DSDC9	100	-	250	4X	-	-	Metal	-	2P+G	-
DSDC2	200	-	250	4X	-	-	Metal	-	2P+G	-
DX1	20	600	-	-	65	-	Metal	-	3P+N+G	-
DX3	32	600	-	-	65	-	Metal	-	3P+N+G	-
DX6	63	600	-	-	65	-	Metal	-	3P+N+G	-
DX9	125	600	-	-	65	-	Metal	-	3P+N+G	-
PXN12c	10	220	-	-	65/66	-	Metal	-	12	-
DXN25c	10	440	-	-	66/67	-	Metal	-	25	-
DXN37c	10	220	-	-	66/67	-	Metal	-	37	-
SPeX	680	1000	-	-	65/66	Poly	-	-	1P	-

...AND SELECTION GUIDE

Model	Current Interruption Rating	Horsepower Ratings (see catalog section for other voltages)			Main Contacts Wire Size Capacity		Terminal Type
		240V - 3Ø	480V - 3Ø	600V - 3Ø	Min	Max	
DXN20	Current Interrupting	2 hp	5 hp	5 hp	16 AWG	10 AWG	Screw
DXN30	Current Interrupting	5 hp	10 hp	15 hp	14 AWG	6 AWG	Screw
DXN60	Current Interrupting	5 hp	20 hp	20 hp	10 AWG	4 AWG	Screw
DXA1	Current Interrupting	-	-	-	16 AWG	10 AWG	Screw
DS20	Non-Current Interrupting	5 hp	7 1/2 hp	10 hp	14 AWG	8 AWG	Screw
DS30	Non-Current Interrupting	5 hp	15 hp	15 hp	14 AWG	4 AWG	Screw
DS60	Non-Current Interrupting	10 hp	25 hp	25 hp	10 AWG	2 AWG	Screw
DS100C	Non-Current Interrupting	20 hp	50 hp	50 hp	10 AWG	2 AWG	Screw
DSN150	Non-Current Interrupting	30 hp	75 hp	75 hp	4 AWG	2/0 AWG	Screw
DS200	Non-Current Interrupting	TBD	TBD	TBD	4 AWG	3/0 AWG	Screw
DR30	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DR50	Non-Current Interrupting	-	-	-	14 AWG	4 AWG	Screw
DR100	Non-Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
DR250	Non-Current Interrupting	-	-	-	4 AWG	4/0 AWG	Screw
DSDC1	Non-Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DSDC3	Non-Current Interrupting	-	-	-	14 AWG	4 AWG	Screw
DSDC6	Non-Current Interrupting	-	-	-	10 AWG	2 AWG	Screw
DSDC9	Non-Current Interrupting	-	-	-	4 AWG	2/0 AWG	Screw
DSDC2	Non-Current Interrupting	-	-	-	4 AWG	3/0 AWG	Screw
DX1	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DX3	Current Interrupting	-	-	-	14 AWG	8 AWG	Screw
DX6	Current Interrupting	-	-	-	6 AWG	1/0 AWG	Screw
DX9	Current Interrupting	-	-	-	1/0 AWG	2/0 AWG	Screw
PXN12c	Non-Current Interrupting	-	-	-	16 AWG	14 AWG	Solder/Crimp
DXN25c	Non-Current Interrupting	-	-	-	16 AWG	14 AWG	Solder/Crimp
DXN37c	Non-Current Interrupting	-	-	-	16 AWG	14 AWG	Solder/Crimp
SPeX	Non-Current Interrupting	-	-	-	2/0 AWG	750 MCM	Lug